

# Elite Valve


elitevalve.com

Customized  
valve solutions  
for the toughest  
applications.

## **E6300 High Pressure, Heavy Slurry Knife Gate Valve**

---

Product Brief



# E6300 High Pressure, Heavy Slurry Knife Gate Valve

The E6300 High Pressure, Heavy Slurry KGV is specifically designed for the mining, cement, and power industries. The double-seat, cavity free design ensures reliable, bidirectional, shut-off in demanding applications that include heavy slurries, rocks, coarse powders, and other abrasive materials. The E6300 is ideally suited for any rubber lined piping application.

## Features & Benefits

- Double-seat, cavity free design allows bidirectional flow/shut-off and eliminates material buildup
- Steel reinforced, natural rubber seats provide zero downstream leakage and are field replaceable to minimize downtime
- Full port opening allows maximum throughput and minimizes pressure drop
- Lubricating wiper ensures smooth gate operation
- Lockout pin and safety covers, included as standard, ensure operator and maintenance safety
- High visibility clevis provides easy identification of valve position
- ISO 5211 mounting pattern allows direct mounting of various actuation options
- Grease fitting on handwheel bearing reduces operating torques




## Technical Details & Standards

- Standard sizes available: 2"– 24" (larger sizes available on request)
- Ductile Iron body
- Polished 316SS gate
- 304SS stem with rolled ACME threads
- Heavy duty yoke with safety screens
- Natural Rubber seats and wiper
- UHMW gate guides
- 300psi pressure rating (maximum 750psi pressure rating with alternate components and materials)
- ASME B16.5 Class 300 flange pattern (alternate flange patterns available on request)
- Canadian CRN

## Options & Accessories

- Higher alloy or hardened gates including 17-4PH, RC50, and Duplex for improved corrosion and wear resistance
- Specialty gate coatings including Xylan 1070, Stellite, or hard chrome for improved wear resistance
- Alternate seat materials including BUNA-N, HNBR, or urethane for process compatibility
- Pneumatic or hydraulic cylinders and electric actuators for automated or remote control
- Bevel gearbox for easy manual operation
- Proximity switches for gate position feedback
- Stem boot to ensure reliable actuation in adverse conditions
- Drain plate with flushing ports to prevent material buildup



© Elite Valve, Oakville, ON, Canada. All rights reserved. All valves information and its contents hereof are proprietary to Elite Valve. Any unauthorized reproduction or disclosure, in whole or in part is strictly prohibited. All valves materials, images and data sheets in this catalogue / brochure is for general information and shall not be used for specific performance data and material selection without first consulting with Elite Valve. Elite Valve reserves the right to change the enclosed valves information without notice. Elite Valve does not accept any liability or damages arising from the use of any valve information within this document. All trademarks and registered trademarks are owned by their respective companies.

23-0004-V4